

Single-Channel Indicator

AI-501 / AI-701



AI-501 / AI-701

Economical
Versatile
Multi-Functional

Main Features

- Measurement Accuracy: 0.2%
- Retransmission Output
- RS-485 Communication
- Multiple Input
- Supports Up to 4 Loops Of Alarms

Applications

- Industrial Ovens
- Plastics Industry
- Hot Stamping Machines
- Packing Equipment
- Control Panel

宇電(香港)自動化科技有限公司

YUDIEN (HK) AUTOMATION TECHNOLOGY CO. LIMITED

12/F, Chun Hoi Comm. Bldg., No.688 Shanghai St., Kln., H.K.

Tel: 27708785 Fax: 27708796

E-Mail : sales@yudian.com.hk

Web Site: www.yudian.com

Single-Channel Indicator

AI-501 / AI-701



Specification

Dimensions

A / A2	96 x 96mm (A2: Light bar to show % of PV)
B	160 x 80mm
C / C3	80 x 160mm (C3: Light bar to show % of PV)
D	72 x 72mm
D2(Only For AI-501)	48 x 48mm
E/E5	48 x 96mm(E5: DIN Rail w/o Display)
F	96 x 48mm

Model	AI-501	AI-701
Inputs		
Thermocouple	K,S,R,E,J,N	K,S,R,E,B,J,N,T
RTD	Pt100	Cu50,Pt100
Linear mV Voltages	1~500mV, 0~100mV, 0~60mV, 0~20mV	0~100mV, 0~60mV, 0~20mV
Linear Voltage	0~5V,0~1V,0~10V,1~5V	0~5V,0~1V,0~10V
Linear Current	0~20mA, 4~20mA	0~20mA, 4~20mA
Linear Resistor	0~80ohms ,0~400ohms	0~80ohms ,0~400ohms
Sampling Time	500ms	250ms

Retransmission Outputs	0~20mA, 4~20mA
Alarm Outputs	Relay - 1A 250V
Measurement Accuracy	0.2%FS +/- 1
Retransmission Accuracy	0.3%FS +/- 1
Resolution	0.0°C / 0.0°F, 0.000 A / V / mA / mV
Communication	RS-485
Supply Power	100-240VAC (50~60Hz) or 24VDC

宇電(香港)自動化科技有限公司

YUDIAN (HK) AUTOMATION TECHNOLOGY CO. LIMITED

12/F, Chun Hoi Comm. Bldg., No.688 Shanghai St., Kln., H.K.

Tel: 27708785 Fax: 27708796

E-Mail : sales@yudian.com.hk

Web Site: www.yudian.com