

SSR25A / SSR40A / SSR40H

Solid State Relay



SSR25A / SSR40A / SSR40H

Economical
Versatile
Multi-Functional

Main Features

With LED Indicator
Zero Cross Turn On
Panel Mount

Applications

- Heater Control
- Light Control Equipment

SSR25A / SSR40A / SSR40H

Solid State Relay



Specification

	SSR25A	SSR40A	SSR40H
Output			
Load Current Range	25A.	40A.	40A.
Load Voltage Range	24~240VAC	24~240VAC	24~415VAC
Dimensions	(58L X 43W X 26H)mm, LED Status Indicator		
Input			
Control Voltage	3V-32V		
Input Current	8mA		
Must Operate Voltage	3V		
Must Release Voltage	1.2V		
Max. Reverse Protection Voltage	24V		
Max. on-state Voltage Drop	0.8V~1.0V		
Max. Leakage Current	10mA		
Max. Turn-On time (@50Hz)	8mS		
Max. Turn-Off time (@50Hz)	8mS		
Min. Off-State dv/dt	500V/ μ s		
Ambient Temperature	-20°C ~85 °C		

宇電(香港)自動化科技有限公司

YUDIAN (HK) AUTOMATION TECHNOLOGY CO. LIMITED

12/F, Chun Hoi Comm. Bldg., No.688 Shanghai St., Kln., H.K.

Tel: 27708785 Fax: 27708796

E-Mail : sales@yudian.com.hk

Web Site: www.yudian.com